




MAXIMUM CABLE LENGTH 350 FT



REMOVE THE PLASTIC NUT FROM STRAIN RELIEF
TO ALLOW MAXIMUM THREAD INSERTION
INTO THE STRAIN RELIEF ADAPTER.

3 FOLD OUTER BRAID SHIELD OVER OUTER JACKET. WHEN CRIMPING THE MODULAR PLUG, OUTER BRAID MUST MAKE CONTACT WITH THE MODULAR PLUG SHIELD AS SHOWN IN DETAIL A.

3 DETAIL A

DETAIL B

UNLESS OTHERWISE SPECIFIED				IN ACCORDANCE WITH THE PRELIMINARY DESIGN			
MATERIAL DESCRIPTION		XXX HOLE SIZE TOLERANCE		DRILL	CHECK	ENGR	APPROV
MATERIAL SIZE		0.000 +0.000 / -0.000		OVER 1500 DATE 3/20/01	DATE	DATE	DATE
FRSH	MASK	AMOL 1/2"	TITLE	CAPLE ASSY- VALVE LVDT.			
THREAD DEPT IS TO FULL THD.		SCALE NONE	3 STAGE (494.16)				
OIL DEPT IS TO MIN. FULL THD.		SCALE NONE	NEXT LEVEL		SIZE	NUMBER	REV
DRILL BITTERS AND SHARP EDGES DO NOT SCALE PRINT		SCALE NONE	PRODUCT CODE		D	572041	XX
M/S SYSTEMS CORPORATION							
CROW SOURCE: HUNTSVILLE, AL							
MATERIAL SPECIFICATION							